

TWO-WIRE SCREW CLAMP W1

CLAMPS AND TIGHTENING SYSTEMS › TWO-WIRE CLAMP

Galvanized steel clamps used for tightening corrugated pipes.

Made with a double steel cable and a tightening force adjustment screw

Ideal for flexible pipes for ventilation and air treatment systems with low wall thickness and raised harmonic steel spiral.

Standard packs of 100 pieces

closing field mm	wire thickness mm	lives
9.5 - 12	1.8	3MA
10.5 - 13	1.8	3MA
11.5 - 14	1.8	3MA
12.5 - 15	1.8	3MA
13.0 - 16	1.8	3MA
13.5 - 17	1.8	3MA
15.0 - 18	1.8	3MA
3.5pm - 7pm	1.8	3MA
17.0 - 20	1.8	3MA
5.5pm - 9pm	1.8	3MA
18.0 - 22	2.2	4MA
19.5 - 23	2.2	4MA
20.0 - 24	2.2	4MA
21.5 - 25	2.2	4MA
22.5 - 26	2.2	4MA
23.5 - 27	2.2	4MA
25.0 - 29	2.2	4MA
27.0 - 31	2.2	4MA
29.0 - 33	2.2	4MA
30.5 - 35	2.2	4MA
33.0 - 37	2.2	4MA
35.5 - 40	2.2	4MA
38.5 - 43	2.2	4MA



Mastertubi.it/q?1345

41.0 - 46	2.5	5MA
43.5 - 49	2.5	5MA
46.5 - 53	2.5	5MA
50.5 - 56	2.5	5MA
53.5 - 60	2.5	5MA
56.5 - 64	2.8	6MA
60.0 - 68	2.8	6MA
64.0 - 72	2.8	6MA
68.5 - 76	2.8	6MA
72.5 - 80	3.0	6MA
76.5 - 84	3.0	6MA
80 - 88	3.0	6MA
88 - 96	3.0	6MA
92 - 100	3.0	6MA
95 - 104	3.0	6MA
98 - 108	3.0	6MA
103 - 112	3.0	6MA
109 - 116	3.0	6MA
111 - 120	3.0	6MA
115 - 124	3.0	6MA
120 - 128	3.0	6MA
124 - 132	3.0	6MA
125 - 140	3.0	6MA
134 - 150	3.0	6MA
145 - 160	3.0	6MA
150 - 165	3.0	6MA
155 - 170	3.0	6MA
165 - 180	3.0	6MA
175 - 190	3.0	6MA