

## TWO-WIRE SPRING CLAMP

CLAMPS AND TIGHTENING SYSTEMS › TWO-WIRE CLAMP


Clamps made with a double galvanized steel wire recommended for pipes with reduced thicknesses and for light seals.

Material type Material description **W1 Galvanized steel** , chromium VI free (EU RoHS directive) D

Recommended for tightening pipes with raised spirals.

They guarantee optimal tightening even in the presence of very soft and thin pipes.

Coating resistance to corrosion (exposure time to salt spray test: 96 HOURS



[Mastertubi.it/q?758](http://Mastertubi.it/q?758)

Ø MIN	Ø IDEAL	Ø MAX	WIRE THICKNESS	BOX
mm	mm	mm	mm	no
5.6	5.6	6.0	0.8	100
6.6	6.8	7.0	1.0	100
7	7.3	7.5	1.0	100
7.3	7.6	7.8	1.0	100
7.8	8.1	8.3	1.0	100
8.3	8.6	8.8	1.0	100
8.8	9.1	9.3	1.0	100
9.3	9.6	9.8	1.0	100
9.8	10.1	10.4	1.2	100
10.4	10.7	11.0	1.2	100
11.0	11.3	11.6	1.2	100
11.6	11.9	12.2	1.5	100
12.2	12.6	12.9	1.5	100
12.4	12.8	13.1	1.2	100

12.9	13.3	13.6	1.5	100
13.3	13.7	14.1	1.5	100
13.6	14	14.4	1.5	100
14.4	14.8	15.1	1.8	100
15.1	15.6	15.9	1.8	100
15.5	15.8	16.3	1.8	100
15.9	16.4	16.8	1.8	100
16.8	17.3	17.7	1.8	100
17.7	18.2	18.7	1.9	100
18.7	19.2	19.5	2.0	100
19.6	20.2	20.5	2.0	100
20.6	21.2	21.6	2.0	100
21.5	22.1	22.6	2.2	100
22	22.6	23.1	2.2	100
22.4	23.1	23.6	2.2	100
23.5	24.2	24.7	2.2	100
24.5	25.2	25.8	2.5	100
25.1	25.8	26.4	2.5	100
25.6	26.3	26.9	2.5	100
26.7	27.5	28.1	2.5	100
27.9	28.7	29.4	2.5	100