

HEAVY DUTY BOLT CLAMP W2

CLAMPS AND TIGHTENING SYSTEMS › HEAVY CLAMP

Bolt collars for high pressures and for reinforced pipes, with spirals or with high hardness.

The bolt is engaged directly on the threaded barrel and it is therefore possible to tighten the collars with electric or pneumatic screwdrivers.

Band with rounded edges. Bridge without slot. Rounded edges.

Band in W2 AISI 430 STAINLESS STEEL - Galvanized steel bolt.

On request also in a version completely in W4 AISI 304 STAINLESS STEEL, or in W5 AISI 316 STAINLESS STEEL.



Mastertubi.it/q?497

| length band mm | thickness band mm | maximum tightening torque Nm | lives | field Of closure |
|-------------------|----------------------|---------------------------------|-------|------------------|
| 18 | 0.6 | 10.2 | M5x35 | 5pm - 7pm |
| | | | | 8pm - 10pm |
| | | | | 23 - 25 |
| 20 | 1.0 | 18.2 | M6x45 | 26 - 28 |
| | | | M6x50 | 29 - 31 |
| | | | | 32 - 35 |
| | | | | 36 - 39 |
| | | | | 40 - 43 |
| | | | | 44 - 47 |
| | | | | 48 - 51 |
| | | | | 52 - 55 |
| | | | M6x55 | 56 - 59 |
| | | | | 60 - 63 |
| | | | | 64 - 67 |
| 25 | 1,2 | | M8x70 | 68 - 73 |
| | | | | 74 - 79 |
| | | | | 80 - 85 |
| | | | | 86 - 91 |
| | | | | 92 - 97 |
| | | | | 98 - 103 |

| | | | | | |
|----|-----|------|--|-------|-----------|
| | | | | | |
| | | | | M8x80 | 104 - 112 |
| | | | | | 113 - 121 |
| | | | | | 122 - 130 |
| | | | | | 131 - 139 |
| | | | | | 140 - 148 |
| | | | | | 149 - 161 |
| | | | | | 162 - 174 |
| | | | | | 175 - 187 |
| | | | | | 188 - 200 |
| | | | | M8x90 | 201 - 213 |
| | | | | | 214 - 226 |
| | | | | | 227 - 239 |
| | | | | | 240 - 252 |
| 25 | 1.5 | 26.3 | | | |