

AUTOMATIC WALL MOUNTED HOSE REEL

HOSE REEL › High pressure hose reel

Spring-loaded hose reel in RED painted steel, suitable for use at distances of maximum 20m (with hose Ø 1/2" - 12.7mm) and maximum 25m (with hose Ø 3/8" - 9.52mm).

The reel comes standard without hose and can be used for rewinding oil, antifreeze, grease, air and water hoses.

On request, version with hydraulic brake-spring kit: i.e. a safety device for the controlled rewinding of the hose applicable on all spring hose reels, avoiding the dangers deriving from an uncontrolled release of the hose during use.

Adjustable wall bracket upon request.



Mastertubi.it/q??

Max pressure Cafe	Attacks - in-out	Useful joint hole mm	pipe diameter OR	tube length m	Weight Kg	Width band mm	Dimensions (LPH) mm
600	M 1/2" - F 1/2"	10	3/8"	15	13	120	260x570x450
			1/2"	20	18	150	260x570x450
			1/2"	25	19	150	260x570x450
100	M 1" - F 1"	20	3/4"	20	27	150	270x600x590
			3/4"	25	30	200	370x640x600
			3/4"	30	38	300	450x540x600
			1"	20	29	150	270x600x590
			1"	25	32	200	370x640x600
			1"	30	40	300	450x540x600