

## AUTOMATIC HOSE REEL FOR DIESEL

HOSE REEL › Hose reel for tankers and fuel

Spring hose reel in painted steel , articulated series with double traction spring.

Suitable for use at distances of up to 20 m for Ø 1"1/4 pipes and 15 m Ø 1"1/2 pipes.

The reel is supplied without hose as standard and can be used for rewinding oil, diesel, air and water hoses. The passage of the fluid occurs through an interchangeable pin in galvanized steel.

On request with AISI 304 or AISI 316 STAINLESS STEEL structure.

On request, version with SPRING\_BRAKE SYSTEM can be supplied

Maximum operating pressure 20 bar



Mastertubi.it/q?

| USEFUL JOINT HOLE<br>mm | MAXIMUM PIPE DIAMETER<br>inch | TUBE LENGTH<br>m | WEIGHT<br>kg | BAND WIDTH<br>mm | DIMENSIONI<br>mm |
|-------------------------|-------------------------------|------------------|--------------|------------------|------------------|
| 25                      | 1"1/4                         | 8                | 18           | 200              | 330x650          |
| 25                      | 1"1/4                         | 20               | 49           | 400              | 590x650          |
| 32                      | 1"1/2                         | 15               | 50           | 400              | 590x650          |
| 25                      | 1"1/4                         | 8                | 18           | 200              | 330x650          |
| 25                      | 1"1/4                         | 20               | 49           | 400              | 330x650          |
|                         |                               |                  |              |                  |                  |

32

1"1/2

15

50

400

330x650