

PUP-P 1.5 TUBE SWEEPER

HOSES › Flexible polyurethane hoses for dust and shavings extraction

use of suction of Pulvirenti products on (municipal vehicle) sweeper or fixed systems

Property:

- Heavy execution
- highly flexible + compressible
- highly abrasion resistant
- Protected and aerodynamically optimised external fold
- resistant to microbes
- excellent cold flexibility
- according to DIN 26057 type 3
- REACH according to -> Technical information / technical / REACH
- RoHS compliant
- Temperature range: -40°C to 90°C
- Pipe with smooth internal profile and corrugated external profile
- armed with harmonic steel wire embedded in the wall
- Wall thickness approx. 1.4 - 1.5 mm depending on diameter
- Packs of 10 meters.



Mastertubi.it/q?1551

DIAMETER INTERNAL	DIAMETER EXTERNAL	PRESSURE	DEPRESSION	RADIUS OF CURVATURE	WEIGHT
mm	mm	bar	bar	mm	Kg/m
160	173	0.365	0.195	200	2.40
180	193	0.385	0.165	260	2.70
203	216	0.367	0.125	330	3.16
225	238	0.335	0.100	364	3.50
254	267	0.285	0.080	407	3.93
275	288	0.270	0.075	425	4.25