

PU WIND HOSE/Heavy - antistatic

HOSES › Flexible polyurethane hoses for dust and shavings extraction

Ester-based polyurethane hose with shock-proof rigid PVC reinforcement spiral covered with polyurethane. Copper cable inserted for the dispersion of surface electric currents. The internal surface is entirely smooth while the external one is corrugated to make the hose flexible to handle.

The ANTISTATIC version includes the cable of 9 copper wires covered with PU on the external surface parallel to the reinforcing coil.

Also available in the non-antistatic version (without incorporated copper wire)

Operating temperature: -40°C +80°C

Color: transparent with gray spiral.

Use: suction of abrasive dust, shavings, plastic granulate.

Polyurethane leaf thickness from Ø 40 to Ø 150 thickness 1mm



| Code | Diameters mm | Weight g/m | mH2O depression | Radius of curvature | Rolls m |
|-----------------|--------------|------------|-----------------|---------------------|---------|
| 11PVPUATPMA038 | 38.1x45.7 | 310 | 3 | 130 | 30 |
| 11PVPUATPPA040 | 40x47 | 350 | 3 | 140 | 30 |
| 11PVPUATPPA045 | 45x52.6 | 445 | 3 | 160 | 30 |
| 11PVPUATPPA052 | 50.8x59.4 | 550 | 3 | 175 | 30 |
| 11PVPUATPPA060 | 60x68.6 | 640 | 3 | 200 | 30 |
| 11PVPUATPPA0630 | 63.5x71.9 | 670 | 3 | 230 | 30 |
| 11PVPUATPPA065 | 65x73.4 | 680 | 3 | 230 | 30 |
| 11PVPUATPPA070 | 70x79.4 | 750 | 3 | 250 | 30 |
| 11PVPUATPPA076 | 76.2x85.6 | 810 | 2.5 | 270 | 30 |
| 11PVPUATPPA080 | 80x90.4 | 900 | 2.5 | 290 | 30 |
| 11PVPUATPPA090 | 90x100.6 | 1050 | 2.5 | 360 | 30 |
| 11PVPUATPPA100 | 100x111.4 | 1290 | 2.5 | 400 | 30 |
| 11PVPUATPPA120 | 120x132 | 1500 | 2.5 | 470 | 30 |