

GARAGEFLEX 200 ARAMID HOSE

HOSES › Gas and hot fume suction pipes

APPLICATIONS

- Flexible hose for hot gases
- Engine exhaust gas extraction: exhaust gas hose reel, suction channel, top exhaust system, floor suction system
- Engine test bench, exhaust gas analysis

PROPERTY

- external protection profile made of elastic material
- Scrub protection from the external clamping profile
- Tight clamping of the wall in the clamping profile
- highly flexible + compressible
- Vibration proof
- excellent heat resistance
- good chemical resistance
- Hardly flammable
- Aramid wall: fire protection class "M1" according to UNE 23.727-90
- RoHS compliant
- REACH based on technical information

TEMPERATURE RANGE

- Exhaust gas temperatures of up to 300°C with correct use of exhaust gas funnels and sufficient fresh air (approx. 50%)

CONSTRUCTION

- CP Design
- Clamping profile support spiral: galvanized steel
- Wall: Specially coated high temperature fabric
- Shockproof and crushproof protection firmly made of high temperature elastic plastic

DELIVERY VARIANTS

- Additional sizes and lengths available upon request
- Special colors: colored spiral
- Stainless steel clamping profile.



Mastertubi.it/q?1412

DIAMETER INTERNAL	DIAMETER EXTERNAL	ABOVE PRESSURE	EMPTY	RADIUS OF CURVATURE	WEIGHT	PACKAGING
inch/mm	mm	bar	bar	mm	Kg/m	m
3"/75-76	89.00	0.42	0.23	48.00	0.87	10
-/80	94.00	0.40	0.20	49.00	0.92	10

4"/100-102	114.00	0.25	0.12	58.00	0.88	10
5"/125-127	139.00	0.22	0.09	70.00	1.09	10
6"/150-152	164.00	0.14	0.05	81.00	1.05	10
8"/200-203	214.00	0.12	0.03	103.00	1.29	10
- /250	264.00	0.08	0.03	125.00	1.64	10