

## PT 125 HOSE

HOSES › Gas and hot fume suction pipes

Flexible hose made of polyamide fabric impregnated with Santoprene with metal reinforcement: spiral incorporated in harmonic steel wire.

Particularly suitable for the extraction of hot and highly chemically aggressive vapours.

Reaction to fire: self-extinguishing class B1 (DIN 4102)

Operating temperature: -20° +125°C (peaks of 150°C)

Color: Black inside-outside.

production diameters: from 40mm to 700mm

Minimum production batches:

- 10 standard meters
- on request up to 20 meters up to Ø 200
- maximum 6 metres for diameters Ø 600 and Ø 700



Mastertubi.it/q?360

Item code	Dimensions OR mm	Pressure of exercise bar	Vacuum packed bar	Radius of curvature mm	Weight g/m
11PVPT0000050	50	0.3	0.10	50	209
11PVPT0000060	60	0.3	0.09	60	255
11PVPT0000070	70	0.25	0.08	70	302
11PVPT0000080	80	0.20	0.07	80	345
11PVPT0000090	90	0.20	0.06	90	377
11PVPT0000100	100	0.15	0.05	100	562
11PVPT0000125	125	0.13	0.04	125	621
11PVPT0000150	150	0.11	0.04	150	683
11PVPT0000160	160	0.10	0.04	160	735
11PVPT0000180	180	0.09	0.03	180	840
11PVPT0000200	200	0.08	0.02	190	940

11PVPT0000250	250	0.07	0.02	220	1175
11PVPT0000300	300	0.05	0.01	260	1327
11PVPT0000350	350	0.04	0.01	310	1548
11PVPT0000400	400	0.04	0.01	360	1769
11PVPT0000450	450	0.03	0.01	390	1990
11PVPT0000500	500	0.03	0.01	420	2212