

SAFETY CLAMP EN 14420 ALUMINUM

CLAMPS AND TIGHTENING SYSTEMS › SAFETY CLAMP - SPANNLOC

"SPANNLOC" type safety clamp in accordance with EN 14420-3 in Aluminum - Steel screws

Maximum working pressure: 25 bar up to DN 125 (for DN 150 and DN 200 the maximum pressure is 16 bar).

The size identifies the closing range compatible with the external diameter of the tube

Attention!

The seal is guaranteed only by tightening smooth pipes externally or on any smooth sleeves at the ends.



Mastertubi.it/q?766

dn	Max pressure	closing field	screws
13	25	22-24	M6x20
19	25	30-33	M6x20
25	25	34-36	M6x20
25	25	36-39	M6x20
25	25	40-43	M6x20
32	25	41-43	M6x20
32	25	43-46	M6x20
32	25	47-50	M6x20
38	25	47-49	M6x20
38	25	50-53	M6x20
38	25	53-56	M6x20
38	25	57-60	M6x20
40	25	53-56	M6x20
40	25	58-61	M6x20
45	25	58-61	M8x25
50	25	59-61	M8x25
50	25	61-63	M8x25
50	25	63-67	M8x25
50	25	69-71	M8x25

63	25	74-76	M8x25
63	25	78-82	M8x25
63	25	84-87	M8x25
75	25	85-89	M8x25
75	25	89-93	M8x25
75	25	94-97	M8x25
75	25	98-101	M8x25
80	25	94-97	M8x25
90	25	101-105	M8x25
100	25	111-115	M10x40
100	25	114-119	M10x40
100	25	118-122	M10x40
100	25	122-126	M10x40
100	25	126-130	M10x40
125	25	143-148	M12x60
150	16	168-174	M12x60
200	16	222-229	M12x60