

IP-FLEX WIRE CLIP BAND 9 W2

CLAMPS AND TIGHTENING SYSTEMS › CLAMP RIDES THE WIRE

Cable ties with endless screw and folding drawer, which guarantee extreme versatility and speed of use, especially on large diameters.

The band is full and fully toothed and the rounded edges protect any damage to the tube. 9mm printed ribbon

W2 steel version

Strip and drawer in 1.4016/AISI430 stainless steel, screw in galvanized steel
Chrome VI free Resistance to corrosion in salt spray minimum 144 h

W4 steel version

All components: belt, drawer, screw in 1.4301/AISI304 stainless steel
Resistance to corrosion in salt spray minimum 240 h

- VERSION FOR HOSES WITH SPIRAL ROTATING CLOCKWISE (RIGHT)
- VERSION FOR TUBES WITH SPIRAL ROTATING ANTICLOCKWISE (SX)

to be specified clearly during the request.

| CODE | Field of application | PACKAGING |
|---------------------|----------------------|-----------|
| 41FAPNTW2-60/110_DX | 60-110 | 10 |
| 41FAPNTW2-60/110_SX | 60-110 | 10 |
| 41FAPNTW2-60/135_DX | 60-135 | 10 |
| 41FAPNTW2-60/135_SX | 60-135 | 10 |
| 41FAPNTW2-60/145_DX | 60-145 | 10 |
| 41FAPNTW2-60/145_SX | 60-145 | 10 |
| 41FAPNTW2-60/170_DX | 60-170 | 10 |
| 41FAPNTW2-60/170_SX | 60-170 | 10 |
| 41FAPNTW2-60/215_DX | 60-215 | 10 |
| 41FAPNTW2-60/215_SX | 60-215 | 10 |
| 41FAPNTW2-60/280_DX | 60-280 | 10 |
| 41FAPNTW2-60/280_SX | 60-280 | 10 |
| 41FAPNTW2-60/325_DX | 60-325 | 10 |
| 41FAPNTW2-60/325_SX | 60-325 | 10 |
| 41FAPNTW2-60/380_DX | 60-380 | 10 |
| 41FAPNTW2-60/380_SX | 60-380 | 10 |



Mastertubi.it/q?1302