

## CAMLOCK TYPE E EN14420-7 - male smooth hose connector

FITTINGS FOR THE CHEMICAL AND FOOD INDUSTRY › CAMLOCK FITTINGS

This type of fitting is designed for the quick and safe joining of two pipes in the shortest possible time.

By inserting the male version inside the FEMALE version you will quickly have a full passage mechanical coupling with the tightening using two lateral levers, whose eccentric on the fulcrum will obtain the definitive locking through a pin or a spring system to obtain the safety stop of the two fins.

The seal is guaranteed by standard gaskets in NBR rubber or different materials depending on the fluid passing through.

The end of this particular fitting consists of a smooth hose holder.

Ideal for use in pressing flexible hoses with THERMOPLASTIC LYNER underlayer such as polyethylene, Crosslinked, PTFE, PFA, PVDF using steel pressing ring nuts which, during the crushing phase, hook onto the ring placed on the hose holder before the fitting to guarantee greater safety against the fitting slipping out.



Mastertubi.it/q?1415

### Available material : AISI 316 STEEL - BRASS

DIAMETER NOMINAL	DIAMETER HOSE HOLDER mm	PRESSURE BAR	STAINLESS STEEL	BRASS
DN019	19	16	X	X
DN025	25	16	X	X
DN032	32	16	X	X
DN040	38	16	X	X
DN050	50	16	X	X
DN065	63	16	X	-
DN080	75	16	X	-
DN100	100	16	X	-