

CAMLOCK FEP-SILICONE CORE GASKET

FITTINGS FOR THE CHEMICAL AND FOOD INDUSTRY › CAMLOCK FITTINGS

ELASTIC SEAL FOR CAM LOCK FEMALE FITTING IN FEP (Fluorinated Ethylene Propylene) WITH SILICONE HEART Weight 40 g - RED COLOR - compliant with RoHs and REAC

| DN | INTERNAL DIAMETER mm | OUTER DIAMETER mm | THICKNESS mm |
|-------|-------------------------|----------------------|-----------------|
| 1/2" | 16.00 +/- 0.3 | 26.30 +/-0.3 | 4.00 +/-0.10 |
| 3/4" | 22.22 +/- 0.3 | 34.93 +/-0.3 | 5.54 +/-0.10 |
| 1" | 26.99 +/- 0.3 | 39.69 +/-0.3 | 6.35 +/-0.10 |
| 1"1/4 | 34.53 +/- 0.3 | 49.21 +/-0.3 | 6.35 +/-0.10 |
| 1"1/2 | 41.27 +/- 0.3 | 55.56 +/-0.3 | 6.35 +/-0.10 |
| 2" | 50.80 +/- 0.3 | 66.67 +/-0.3 | 6.35 +/-0.10 |
| 2"1/2 | 60.32 +/- 0.3 | 79.37 +/-0.3 | 6.35 +/-0.10 |
| 3" | 76.20 +/- 0.4 | 94.45 +/-0.4 | 6.35 +/-0.10 |
| 4" | 101.30 +/- 0.4 | 123.30 +/-0.4 | 6.35 +/-0.10 |
| 5" | 127.00 +/- 0.4 | 150.30 +/-0.4 | 6.35 +/-0.10 |
| 6" | 152.40 +/- 0.5 | 179.83 +/-0.5 | 6.35 +/-0.10 |
| 8" | 237.00 +/- 0.5 | 237.30 +/-0.5 | 9.50 +/-0.10 |



Mastertubi.it/q?970