

SCH60 LOK SERIES CHECK VALVE - working pressure up to 413 b

PIPES AND FITTINGS FOR HYDROGEN AND FUEL CELLS › STAINLESS STEEL SAFETY CONNECTIONS › CHECK VALVE

CODE		HOLE mm	TERMINAL	
			measure	entry/exit
SCH1	S-2T	4.8	1/8"	S-LOK
	S-4T		1/4"	S-LOK
	S-6M		6mm	S-LOK
	F-4N		1/4"	Female NPT
	M-2N		1/8"	NPT male
	M-4N		1/4"	NPT male
SCH2	S-6T	7.8	3/8"	S-LOK
	S-8T		1/2"	S-LOK
	S-8M		8mm	S-LOK
	S-10M		10mm	S-LOK
	S-12M		12mm	S-LOK
	F-6N		3/8"	Female NPT
	F-8N		1/2"	Female NPT
	M-6N		3/8"	NPT male
	M-8N		1/2"	NPT male
	F-8R		1/2"	ISO female
	M-8R		1/2"	ISO male
	S-12T		3/4"	S-LOK
	S-16T		1"	S-LOK
	S-22M		22mm	S-LOK
	S-25M		25mm	S-LOK
	F-12N		3/4"	Female NPT
	F-16N		1"	Female NPT

SCH3		15.0		
	M-12N		3/4"	NPT male
	M-16N		1"	NPT male
	F-12R		3/4"	ISO female
	F-16R		1"	ISO female
	M-12R		3/4"	ISO male
	M-16R		1"	ISO male