

## SPIRALIN\_HT

### SPIRAL

Spiral and shaped curved flat band in rigid shock-proof POLYAMIDE (PA). Ideal for wrapping and containing bundles of hydraulic and hydraulic pipes and electrical wiring. Excellent resistance to abrasion, crushing, ultraviolet rays, ozone and flame.

Complies with UL94 HB self-extinguishing class

Operating temperature:  $-10^{\circ}$   $+125^{\circ}\text{C}$

Elongation at break: 50%

Density:  $1.12 \text{ g/cm}^3$  (ISO 1183)

Viscosity:  $228 \text{ cm}^3$  (ISO307)

Elasticity:  $3.300/1500 \text{ Mpa}$  (ISO 527-2)

Flexural strength:  $110/30 \text{ Mpa}$  (ISO)

Electrical Resistance: 10 and 13 O



[Mastertubi.it/q?1155](http://Mastertubi.it/q?1155)

diameter internal mm	diameter external mm	weight theoretical kg/m	length roll m
8	12	0.04	50
13	16	0.05	50
16	20	0.07	50
19	25	0.09	50
22	27	0.12	50
25	29	0.14	50
27	32	0.15	50
30	35	0.17	50
35	40	0.21	50
44	50	0.32	25
56	63	0.61	20
67	75	0.75	20
80	90	1.30	10