

LIGHTWEIGHT SHEATH IN FIBERGLASS AND SILICONE

INSULATING SHEATH IN TECHNICAL FABRIC

CHARACTERISTICS

Temperature class **C**

Continuous operating temperature: -60° +250°

Dielectric strength: 1.5 kV to 7 kV

Flammable and self-extinguishing

Good resistance in the presence of flames, splashes of molten metal or glass, steam flows.

Excellent flexibility even at low temperatures.

Good resistance to UV rays

Asbestos free

Halogen free - waterproof - Thermal insulator

Resistant to transformer oils

Good compatibility with paints and solvents



Mastertubi.it/q?1213

Reference STANDARDS

- Compliant with the RoHS directive
- Complies with the Reach directive
- EN 60695-2-10 (05-2001)
- EN 60695-2-11 (07-2001)
- EN (CEI) 60684-3 SHEETS 400 A 402 (02/2003)
- EN 60684-1 (10-2003)
- EN 60684-2 (07-2012)
- UI 1441 / CSA C22.2 N° 198.3 15C UL Listed: Approved with VW-1 flame retardant test (vertical test) File number: UZIQ2 - E330510

- Sheath diameters: from Ø 0.5 to Ø 33mm

- Standard brick red colour

- Other colours: green, blue, black, yellow, white, grey, brown.

AVAILABLE DIAMETERS

0.50 - 0.80 - 1 - 1.50 - 2 - 2.50 - 3 - 3.50 - 4 - 5 - 6 - 7 - 8 - 9 - 10 - 12 - 14 - 16 - 18 - 20 - 22 - 22 - 25 - 30