

## TRELLVAC EXTRACTOR HD HOSE

HOSES › Flexible rubber hoses for passage of industrial abrasives

Applications: handling hose for suction of chips, sand, universal material dust, and dust, etc. Applications include hardwood, chip board, and wood veneer plants, Fiberboard plants, etc. Advantages: Light and flexible design with steel spiral.

Good bending radius. P

particularly useful when low weight and easy handling in combination with good abrasion resistance are valued.

Inside: SBR / NR wear resistant, black, smooth

Reinforcement: synthetic wire with embedded steel spiral

Cover: wear and weather resistant SBR / NR, black, corrugated

Working temperature -40° to +90° C.

Electrical properties: conductive substrate and cover,  $R < 10^6 \hat{\Omega}/m$ .

Packaging/Packaging 12 meter rolls.

Additional information: External diameter measured at the top of the corrugation.

Technical specifications



Mastertubi.it/q?429

Dimension Ø mm	Depression maximum Cafe	Radius of curvature mm	Weight Kg/m
38x47	0.90	50	0.73
51x60	0.90	75	0.96
63x72	0.90	100	1.13
76x86	0.9	120	1.37
102x111	0.9	150	1.85
127x136	0.7	175	2.33
152x161	0.4	200	2.77

□  $\phi$  is subject to availability. \* Length tolerance:  $\pm 1\%$  (ISO 1307 Standard)