

STRAIGHT CONICAL MALE BSPT NICKEL PLATED

FITTINGS FOR COMPRESSED AIR › FITTINGS AND CONNECTIONS FOR PNEUMATIC SYSTEMS › 100 Series
PNEUMATIC QUICK FITTINGS IN NICKEL PLATED BRASS METALLIC PUSH

OTRC-R

art. 100_1 OTRC-R

STRAIGHT CONICAL MALE BSPT NICKEL PLATED


Operating Temperature: -20 °C to 80 °C

Construction Materials: Nickel-plated brass UNI EN 12164 CW 614N and UNI EN 12165 CW 617N

Usable tubes: Polyamide tube · Polyethylene tube · Polyurethane tube Oring types: NBR without silicone

Compatible Fluids: Air · Compressed Air · Vacuum · Operating Pressure: 16 Bar

Standard pack 10 pieces.



Mastertubi.it/q?1314

CODE	Tube	fillet steak	Length	Key	WEIGHT
	mm	conical	mm	CH	g
OTRC04R01	4	R1/8"	18.5	10	7
OTRC04R02	4	R1/4"	20	14	15
OTRC06R01	6	R1/8"	21	12	9
OTRC06R02	6	R1/4"	20	14	14
OTRC08R01	8	R1/8"	26	14	15
OTRC08R02	8	R1/4"	24	14	14
OTRC08R03	8	R3/8"	22	17	24
OTRC10R02	10	R1/4"	31	16	22
OTRC10R03	10	R3/8"	26	17	23
OTRC10R04	10	R1/2"	26.5	22	45
OTRC12R02	12	R1/4"	33	19	21
OTRC12R03	12	R3/8"	29.5	19	27
OTRC12R04	12	R1/2"	27	22	44.5