

NICKEL PLATED BSPP CYLINDRICAL MALE STRAIGHT

FITTINGS FOR COMPRESSED AIR › FITTINGS AND CONNECTIONS FOR PNEUMATIC SYSTEMS › 100 Series
PNEUMATIC QUICK FITTINGS IN NICKEL PLATED BRASS METALLIC PUSH

OTRC-G

art. 100_2 OTRC-G

NICKEL PLATED BSPP CYLINDRICAL MALE STRAIGHT




Operating Temperature: -20 °C to 80 °C

Construction Materials: Nickel-plated brass UNI EN 12164 CW 614N and UNI EN 12165 CW 617N

Usable tubes: Polyamide tube · Polyethylene tube · Polyurethane tube Oring types: NBR without silicone

Compatible Fluids: Air · Compressed Air · Vacuum · Operating Pressure: 16 Bar

Standard pack 10 pieces.



Mastertubi.it/q?1318

CODE	Tube	fillet steak	Length	Key	WEIGHT
	mm	conical	mm		gr.
OTRC04M5	4	M5x0.8	19	9	5
OTRC04G01	4	G1/8"	18.0	10	8
OTRC04G02	4	G1/4"	18.0	10	11
OTRC06M5	6	M5x0.8	21.0	11	8
OTRC06G01	6	G1/8"	19.5	12	9
OTRC06G02	6	G1/4"	19.5	12	12
OTRC08G01	8	G1/8"	24.5	14	14
OTRC08G02	8	G1/4"	21.5	14	13.5
OTRC08G03	8	G3/8"	21.5	14	20
OTRC10G02	10	G1/4"	27.5	16	19
OTRC10G03	10	G3/8"	25.0	16	22
OTRC10G04	10	G1/2"	25.0	16	33
OTRC12G02	12	G1/4"	30.0	19	28
OTRC12G03	12	G3/8"	29.5	19	30

OTRC12G04	12	G1/2"	28.0	19	37
-----------	----	-------	------	----	----