

NICKEL PLATED NPT CONICAL MALE STRAIGHT

FITTINGS FOR COMPRESSED AIR › FITTINGS AND CONNECTIONS FOR PNEUMATIC SYSTEMS › 100 Series
PNEUMATIC QUICK FITTINGS IN NICKEL PLATED BRASS METALLIC PUSH

OTRC-N

art. 100_3 OTRC-N

STRAIGHT MALE THREADED NPT INCH in NICKEL PLATED BRASS




Operating Temperature: -20 °C to 80 °C

Construction Materials: Nickel-plated brass UNI EN 12164 CW 614N and UNI EN 12165 CW 617N

Usable tubes: Polyamide tube · Polyethylene tube · Polyurethane tube Oring types: NBR without silicone

Compatible Fluids: Air · Compressed Air · Vacuum · Operating Pressure: 16 Bar



Standard pack 10 pieces.



Mastertubi.it/q?1319

CODE	Tube	fillet steak	Length	Key	WEIGHT
	inch	NPT	mm	CH	g
OTRC532N01	5/32"	N1/8"	19.0	7/16"	9.0
OTRC532N02	5/32"	N1/4"	20.5	9/16"	16.0
OTRC1-4N01	1/4"	N1/8"	22.5	1/2"	11.0
OTRC1-4N02	1/4"	N1/4"	22.5	9/16"	15.0
OTRC516N01	5/16"	N1/8"	27.0	9/16"	15.5
OTRC516N02	5/16"	N1/4"	25.5	6/16"	16.0
OTRC516N03	5/16"	N3/8"	23.5	11/16"	25.0
OTRC38N01	3/8"	N1/8"	29.0	11/16"	21.5
OTRC38N02	3/8"	N1/4"	30.0	11/16"	25.0
OTRC38N03	3/8"	N3/8"	26.0	11/16"	24.0
OTRC38N04	3/8"	N1/2"	27.0	7/8"	46.0
OTRC1-2N02	1/2"	N1/4"	34.0	7/8"	37.0
OTRC1-2N03	1/2"	N3/8"	34.5	7/8"	39.0
OTRC1-2N04	1/2"	N1/2"	30.5	7/8"	43.0