

## METRIC ROUND NICKEL PLATED MALE STRAIGHT

FITTINGS FOR COMPRESSED AIR › FITTINGS AND CONNECTIONS FOR PNEUMATIC SYSTEMS › 100 Series  
PNEUMATIC QUICK FITTINGS IN NICKEL PLATED BRASS METALLIC PUSH

OTROC-G

### art. 100\_4 OTROC-G

### NICKEL PLATED METRIC ROUND MALE STRAIGHT FOR METRIC PIPE




Operating Temperature: -20 °C to 80 °C

Construction Materials: Nickel-plated brass UNI EN 12164 CW 614N and UNI EN 12165 CW 617N

Usable tubes: Polyamide tube · Polyethylene tube · Polyurethane tube Oring types: NBR without silicone

Compatible Fluids: Air · Compressed Air · Vacuum · Operating Pressure: 16 Bar

Standard pack 10 pieces.



Mastertubi.it/q?1320

CODE	Tube	fillet steak	Length	Key	WEIGHT
	mm	conical	mm		gr
OTRC04M5	4	M5x0.8	19.0	2.50	5
OTRC04M6	4	M6x1	20.0	2.50	8
OTRC04M7	4	M7x1	20.5	2.50	11
OTRC06M5	6	M5x0.8	21.1	2.50	8
OTRC06M7	6	M7x1	20.5	4	9