

STRAIGHT CYLINDRICAL FEMALE BSPP

FITTINGS FOR COMPRESSED AIR › FITTINGS AND CONNECTIONS FOR PNEUMATIC SYSTEMS › 100 Series
PNEUMATIC QUICK FITTINGS IN NICKEL PLATED BRASS METALLIC PUSH

art. 100_6 OTRCF-G NICKEL PLATED BSPP CYLINDRICAL FEMALE STRAIGHT FOR METRIC PIPE



Operating Temperature: -20 °C to 80 °C

Construction Materials: Nickel-plated brass UNI EN 12164 CW 614N and UNI EN 12165 CW 617N

Usable tubes: Polyamide tube · Polyethylene tube · Polyurethane tube Oring types: NBR without silicone

Compatible Fluids: Air · Compressed Air · Vacuum · Operating Pressure: 16 Bar

Standard pack 10 pieces.



Mastertubi.it/q?1324

CODE	Tube	fillet steak	Length	Key
	mm	inch	mm	
OTRCF04G01	4	G 1/8"	24.50	10
OTRCF04G02	4	G 1/4"	28.50	10
OTRCF06G01	6	G 1/8"	26.10	12
OTRCF06G02	6	G 1/4"	29.60	12
OTRCF08G01	8	G 1/8"	27.20	14
OTRCF08G02	8	G 1/4"	32.20	14