

BSPT TAPERED MALE SWIVEL ELBOW

FITTINGS FOR COMPRESSED AIR › FITTINGS AND CONNECTIONS FOR PNEUMATIC SYSTEMS › 100 Series
PNEUMATIC QUICK FITTINGS IN NICKEL PLATED BRASS METALLIC PUSH

OTRL-R

art. 100_9 OTRL-R

NICKEL PLATED BSPT CONICAL SWIVEL MALE ELBOW FOR METRIC PIPE



Operating Temperature: -20 °C to 80 °C

Construction Materials: Nickel-plated brass UNI EN 12164 CW 614N and UNI EN 12165 CW 617N

Usable tubes: Polyamide tube · Polyethylene tube · Polyurethane tube Oring types: NBR without silicone

Compatible Fluids: Air · Compressed Air · Vacuum · Operating Pressure: 16 Bar

Standard pack 10 pieces.



Mastertubi.it/q?1328

CODE	Tube	fillet steak	Length	Key	WEIGHT
	mm	conical	mm	CH	g
OTRL04R01	4	R 1/8"	18.5	13	20.0
OTRL04R02	4	R 1/4"	20	14	23.0
OTRL06R01	6	R 1/8"	21	13	20.0
OTRL06R02	6	R 1/4"	20	14	24.0
OTRL08R01	8	R 1/8"	26	13	22.0
OTRL08R02	8	R 1/4"	24	14	26.0
OTRL08R03	8	R 3/8"	22	17	32.0
OTRL10R02	10	R 1/4"	31	16	41.0
OTRL10R03	10	R 3/8"	26	17	45.0
OTRL10R04	10	R 1/2"	26.5	22	59.0
OTRL12R02	12	R 1/4"	33	20	56.0
OTRL12R03	12	R 3/8"	29.5	20	59.0
OTRL12R04	12	R 1/2"	27	22	70.0