

BSPP CYLINDRICAL SWIVEL MALE ELBOW

FITTINGS FOR COMPRESSED AIR › FITTINGS AND CONNECTIONS FOR PNEUMATIC SYSTEMS › 100 Series
PNEUMATIC QUICK FITTINGS IN NICKEL PLATED BRASS METALLIC PUSH

art. 100_10 OTRL-G

NICKEL PLATED BSPT CONICAL SWIVEL MALE ELBOW FOR METRIC PIPE



Operating Temperature: -20 °C to 80 °C

Construction Materials: Nickel-plated brass UNI EN 12164 CW 614N and UNI EN 12165 CW 617N

Usable tubes: Polyamide tube · Polyethylene tube · Polyurethane tube Oring types: NBR without silicone

Compatible Fluids: Air · Compressed Air · Vacuum · Operating Pressure: 16 Bar

Standard pack 10 pieces.

CODE	Tube	fillet steak	Length	Key	WEIGHT
	mm	conical	mm	CH	g
OTRL04M5	4	M5x0.8	18.0	8	5.0
OTRL04G01	4	G 1/8"	19.5	13	19.0
OTRL04G02	4	G 1/4"	19.5	13	22.0
OTRL06M5	6	M5x0.8	19.5	8	11.0
OTRL06G01	6	G 1/8"	21	13	20.0
OTRL06G02	6	G 1/4"	21	13	24.0
OTRL08G01	8	G 1/8"	23	13	22.0
OTRL08G02	8	G 1/4"	23	13	24.0
OTRL08G03	8	G 3/8"	23	13	28.0
OTRL10G02	10	G 1/4"	26	16	35.0
OTRL10G03	10	G 3/8"	26	16	43.5
OTRL10G04	10	G 1/2"	26	16	52.0
OTRL12G02	12	G 1/4"	31	20	55.0
OTRL12G03	12	G 3/8"	31	20	55.0
OTRL12G04	12	G 1/2"	31	20	63.0



Mastertubi.it/q?1329

Nickel plated BSPP cylindrical male swivel elbow for inch pipe

CODE	Tube	fillet steak	Length	Key	WEIGHT
	inch	inch	mm		gr
OTRL1-4G01	1/4"	G 1/8"	22.0	13	20.0
OTRL1-4G02	1/4"	G 1/4"	22.0	13	24.0
OTRL38G02	3/8"	G 1/4"	26.0	16	35.0
OTRL38G03	3/8"	G 3/8"	26.0	16	43.5