

MALE SWIVEL ELBOW NPT & UNF

FITTINGS FOR COMPRESSED AIR › FITTINGS AND CONNECTIONS FOR PNEUMATIC SYSTEMS › 100 Series PN QUICK FITTINGS IN NICKEL PLATED BRASS METALLIC PUSH

OTRL-N

art. 100_9 OTRL-R

NPT & UNF NICKEL PLATED MALE SWIVEL ELBOW FOR METRIC PIPE

Operating Temperature: -20 °C to 80 °C

Construction Materials: Nickel-plated brass UNI EN 12164 CW 614N and UNI EN 12165 CW 617N

Usable tubes: Polyamide tube · Polyethylene tube · Polyurethane tube Oring types: NBR without silicone

Compatible Fluids: Air · Compressed Air · Vacuum · Operating Pressure: 16 Bar

Standard pack 10 pieces.



Mastertubi.it/q?1

CODE	Tube	fillet steak	Length	Key	WEIGHT
	mm	NPT	mm	CH	g
OTRL532UF1032	5/32"	UNF 10/32"	18.0	3/8"	11.0
OTRL532N01	5/32"	N 1/8"	19.5	9/16"	20.5
OTRL532N02	5/32"	N 1/4"	19.5	9/16"	24.0
OTRL1-4N01	1/4"	N 1/8"	21.5	9/16"	23.0
OTRL1-4N02	1/4"	N 1/4"	21.5	9/16"	26.0
OTRL1-6N01	5/16"	N 1/8"	23.5	9/16"	23.0
OTRL1-6N02	5/16"	N 1/4"	23.5	9/16"	24.0
OTRL1-6N03	5/16"	N 3/8"	23.5	11/16"	34.0
OTRL38N01	3/8"	N 1/8"	26.0	11/16"	40.0
OTRL38N02	3/8"	N 1/4"	26.0	11/16"	43.0
OTRL38N03	3/8"	N 3/8"	26.0	11/16"	47.0
OTRL38N04	3/8"	N 1/2"	26.0	7/8"	60.0
OTRL1-2N02	1/2"	N 1/4"	31.0	7/8"	58.0
OTRL1-2N03	1/2"	N 3/8"	31.0	7/8"	61.0
OTRL1-2N04	1/2"	N 1/2"	31.0	7/8"	67.0