

CONICAL SWIVEL CENTRAL MALE T BSPT

FITTINGS FOR COMPRESSED AIR › FITTINGS AND CONNECTIONS FOR PNEUMATIC SYSTEMS › 100 Series
PNEUMATIC QUICK FITTINGS IN NICKEL PLATED BRASS METALLIC PUSH

CONICAL SWIVEL CENTRAL MALE T BSPT

Operating Temperature: -20 °C to 80 °C


Construction Materials: Nickel-plated brass UNI EN 12164 CW 614N and UNI EN 12165 CW 617N

Usable tubes: Polyamide tube · Polyethylene tube · Polyurethane tube
Oring types: NBR without silicone

Compatible Fluids: Air · Compressed Air · Vacuum · Operating Pressure: 16 Bar

Standard pack 10 pieces.

OTRT-R



Mastertubi.it/q?1344

| CODE | Tube | fillet steak | Length | WEIGHT |
|-----------|------|-----------------|--------|--------|
| | mm | BSPT | mm | g |
| OTRT04R01 | 4 | R 1/8" | 39.0 | 27.0 |
| OTRT04R02 | 4 | R 1/4" | 39.0 | 31.0 |
| OTRT06R01 | 6 | R 1/8" | 42.0 | 30.0 |
| OTRT06R02 | 6 | R 1/4" | 42.0 | 34.0 |
| OTRT08R01 | 8 | R 1/8" | 46.5 | 34.0 |
| OTRT08R02 | 8 | R 1/4" | 46.5 | 37.0 |
| OTRT08R03 | 8 | R 3/8" | 46.5 | 44.0 |
| OTRT10R02 | 10 | R 1/4" | 52.0 | 55.0 |
| OTRT10R03 | 10 | R 3/8" | 52.0 | 58.5 |
| OTRT10R04 | 10 | R 1/2" | 52.0 | 73.0 |
| OTRT12R02 | 12 | R 1/4" | 62.0 | 77.0 |
| OTRT12R03 | 12 | R 3/8" | 62.0 | 80.0 |
| OTRT12R04 | 12 | R 1/2" | 62.0 | 81.0 |