

FLATTENABLE RUBBER HOSE 10 bar

HOSES › Flattenable tubes

Rubber hose for water and inert fluid delivery, flattenable. Useful for irrigating fields or transferring water through submersible pumps in non-corrosive fluids. Due to its lightness and flattenability, it is ideal for use in mobile sprinkler irrigation systems.

STRUCTURE

- Underlayer: smooth black SBR rubber.
- Reinforcements: high-strength synthetic fabrics.
- Cover: black rubber with SBR canvas impression, resistant to abrasion and atmospheric agents.
- Surface: smooth with canvas impression.
- Operating temperature: -30°C +80°



[Mastertubi.it/q?1022](https://www.mastertubi.it/q?1022)

INTERNAL DIAMETER mm	EXTERNAL DIAMETER mm	THEORETICAL WEIGHT Kg/m	PRESSURE OF EXERCISE bar	PRESSURE OF EXPLOSION bar	ROLLS LENGTH m
40	46	0.55	10	30	20/40/61
45	51	0.58	10	30	20/40/61
51	57	0.69	10	30	20/40/61
60	67	0.94	10	30	20/40/61
60	69	1.30	20	60	20/40/61
70	77	1.09	10	30	20/40/61
76	83	1.18	10	30	20/40/61
80	87	1.24	10	30	20/40/61
80	91	1.99	20	60	20/40/61
90	97	1.39	10	30	20/40/61
102	109	1.57	10	30	20/40/61
102	113	2.51	20	60	20/40/61
120	128	2.10	10	30	20/40/61
152	160	2.65	10	30	20/40/61
152	163	3.67	20	60	20/40/61
203	215	5.32	10	30	20/40
254	267	7.18	10	30	20
305	319	9.26	10	30	20
350	365	10.70	5	15	20
400	417	13.00	5	15	12
457	476	18.40	5	15	12

500	524	23.75	5	15	12
609	635	31.20	5	15	12