

PA12 PHL HOSE - LONGLIFE

HOSES › Hoses for Pneumatic Applications › POLYAMIDE TUBES - RILSAN PA11 - PA12

Flexible linear tube in **POLYAMIDE 12** of chemical origin.
PHL (light-stable and plasticized) according to DIN
73378/74324



Industrial applications: automation, industrial vehicle
braking systems, systems.

Available colors: neutral, yellow, blue, red, green, black,
light blue, orange.

Operating temperature. -40°C to +80°C

On request also available in special versions:

- MULTITUBE
- Braided with galvanized sheath, with glass fiber or silicone

Packaging: standard polyethylene film or cardboard box or wooden spools.



Mastertubi.it/q?400

TABLE OF PRESSURES AS A FUNCTION OF TEMPERATURES:

20°	40°	60°	80°
100%	85%	60%	40%

Item number	OR mm	Curvature radius mm	Bar operating pressure	Burst pressure bar
03PA110002/04	2x4	20	44	133
03PA1102,5/04	2.5x4	25	31	ninety two
03PA1102,7/04	2.7x4	25	26	78
03PA110004/06	4x6	30	27	80
03PA110005/08	5x8	40	31	ninety two
03PA110006/08	6x8	40	19	57
03PA110006/10	6x10	55	33	100

03PA110007/10	7x10	55	24	71
03PA1107,5/10	7.5x10	60	19	57
03PA110008/10	8x10	60	15	44
03PA110009/12	9x12	60	19	57
03PA110010/12	10/12	85	12	36
03PA110010/14	10x14	75	22	67
03PA110011/14	11x14	85	16	48
03PA110011/15	11x15	85	21	62
03PA110012/15	12x15	90	15	44
03PA110012/16	12x16	95	19	57
03PA110014/18	14x18	100	17	50