

PA12 PHL Y BRAKE AIR HOSE

HOSES › Hoses for Pneumatic Applications › POLYAMIDE TUBES - RILSAN PA11 - PA12

semi-flexible Polyamide 12 tube of PHL Y chemical origin: plasticized, stabilized to temperature and light with high burst pressure and impact resistance at low temperatures. Raw material made to meet the DIN 73378/74324 standard.



APPLICATIONS:

Industrial automation; Empty; Chemical resistance; Low permeability; Disinfestation lines; Transfer of petroleum derivatives; Clutch system; Trailer/trailer brake system; Resistance to hydrolysis.



Mastertubi.it/q?990

TEMPERATURE varying from **-40°C to 80°C**.

Colors: BLUE, YELLOW, NEUTRAL, RED

Packaging: IN ROLLS OF 100 METERS OR IN CARDBOARD BOXES OF 25-50 METERS

CODE	Ø internal mm	Ø ext. mm	Wall thickness mm	Weight g/m	Minimum radius of curvature mm	WP Cafe	BP Cafe
12PHLY4X6	6	4	1	16.4	30	108	36
12PHLY6X8	8	6	1	22.8	55	77	25
12PHLY6X9	9	6	1.5	36.7	45	108	36
12PHLY6X10	10	6	2	52.2	40	135	45
12PHLY7X10	10	7	1.5	41.6	55	95	31
12PHLY7.5X10	10	7.5	1.25	35.7	65	77	25
12PHLY8X10	10	8	1	29.4	85	60	20
12PHLY9X12	12	9	1.5	51.4	80	77	25
12PHLY10X14	14	10	2	78.4	80	90	30
12PHLY11X15	15	11	2	84.9	90	83	27
12PHLY12X15	15	12	1.5	66.1	125	60	20
12PHLY12X16	16	12	2	91.4	105	77	25
12PHLY14X18	18	14	2	104.5	135	67	22