

POLYURETHANE HOSE - EXTRAFLEX C98 ANTI UV

HOSES › Hoses for Pneumatic Applications › POLYURETHANE - ELASTOLLAN - EXTRAFLEX HOSES

Polyurethane elastomer of ETHER based chemical origin, excellent flexibility at low temperatures, limited deformation, excellent hydrolytic stability, resistance to hydrocarbons, excellent abrasive resistance.



Hardness 98 ShoreA

It is used for compressed air, as an insulating element, as a seal in hydraulic systems.

Operating temperature: -40°C +60°C.



Mastertubi.it/q?1161

TRANSPARENT colours : neutral, light blue, black, red, green, dark blue.

Diameter internal mm	Diameter external mm	Thickness mm	radius minimum mm	Pressure of exercise Cafe	Colors Transparent
2.50	4	0.75	15	12	blue-transparent-light blue
3.80	6	1.00	25	10	black-blue-red-transparent-light blue
5.00	8	1.50	30	12	blue-transparent-light blue
5.50	8	1.25	40	9	black-blue-red-transparent-light blue
6.50	10	1.75	40	11	blue-transparent
7.00	10	1.50	50	9	black-blue-transparent-light blue
7.50	10	1.25	60	7	blue-green-transparent-light blue
8.00	12	2.00	50	10	blue-red-transparent-light blue
9.00	12	1.50	70	7	blue-transparent-light blue