

## POLYURETHANE HOSE - ELASTOLLAN C98

HOSES › Hoses for Pneumatic Applications › POLYURETHANE - ELASTOLLAN - EXTRAFLEX HOSES

Polyurethane elastomer of ESTER based chemical origin, excellent flexibility at low temperatures, limited deformation, excellent hydrolytic stability, resistance to hydrocarbons, excellent abrasive resistance. Hardness 52 ShoreD.

Suitable for use with quick-connect fittings.

It is used for compressed air, as an insulating element, as a gasket in hydraulic systems.

Operating temperature: -40°C +60°C.

Colours: neutral, **light blue**, black, red, yellow, green, orange, grey.



Mastertubi.it?q?395

Code	Diameter mm	Radius of curvature mm	Pressure exercise Cafe
03EX950002/04	2x4	10	22
03EX9802.5/04	2.5x4	15	15
03EX982.7/4.3	2.7x4.3	20	15
03EX950003/05	3x5	20	16
03EX950004/06	4x6	25	14
03EX980005/08	5x8	30	15
03EX9805.5/08	5x8	40	12
03EX980006/08	6x8	40	11
03EX9806.5/10	6x10	40	14
03EX980007/10	7x10	35	11
03EX98007.5/10	7.5x10	60	9
03EX980008/10	8x10	65	8
03EX980008/12	8x12	50	13
03EX980009/12	9x12	70	9
03EX980009/12	11x14	100	8