

EXTRAFLEX 1185 CRT POLYURETHANE HOSE

HOSES › Hoses for Pneumatic Applications › POLYURETHANE - ELASTOLLAN - EXTRAFLEX HOSES

Linear hose in self-lubricated antistatic polyurethane with textile reinforcement, multilayer flexible ether-based polyurethane resistant to hydrolysis and microbial corrosion. Internal reinforcement with glued high tenacity POLYESTER FIBER braid, rhombic mesh for maximum resistance to pressure.

Hardness 85 shoreA - Operating temperature: -40° +60°C

Excellent pressure resistance pressure safety factor: 3:1

Recommended for use with hose barb fittings and clamps.

Available colors: BLUE - RED

PACKAGING: ROLLS OF 100 meters - CARDBOARD BOX IN ROLLS OF 25 - 50 METERS

| Code | Dimension mm | Weight g/m | Radius of curvature mm | Pressure exercise Cafe | colors |
|-----------------|-----------------|---------------|------------------------------|------------------------------|----------|
| 03EX90TR5.5/8 2 | 5.5x8 | 30.5 | 40 | 13 | blue-red |
| 03EX90TR6.5/10 | 6.5x10 | 52.2 | 40 | 20 | blue |
| 03EX90TR7.5/10 | 7.5x10 | 39.4 | 55 | 40 | blue |
| 03EX90TR8/12 | 8x12 | 72.3 | 50 | 20 | blue-red |
| 03EX90TR10/14.5 | 10x14.5 | 99.7 | 70 | 15 | blue |
| 03EX90TR11/16 | 11x16 | 122.2 | 75 | 15 | blue |
| 03EX90TR13/18 | 13x18 | 140.2 | 100 | 15 | blue |
| 03EX90TR13/19 | 13X19 | 173.8 | 85 | 15 | blue |