

LOW DENSITY POLYETHYLENE - LDPE

HOSES › Hoses for Pneumatic Applications › POLYETHYLENE PIPES

Flexible linear tube for pneumatic rice - LOW DENSITY POLYETHYLENE - flexible and light-stabilised.

SAFETY PRESSURE 3:1

INDICATIVE TEMPERATURE FOR USE: -10°C+60°C

available colors: NEUTRAL - Light blue - BLUE - YELLOW - BLACK - RED - GREEN

package lengths: standard 100m - over Øe 24 50m

Upon request, it can be supplied in the MULTI-TUBE version with containment sheath.



Mastertubi.it/q?864

DIMENSIONS mm	WEIGHT g/m	RADIUS OF CURVATURE mm	PRESSURE MAXIMUM AT 20° C Cafe
1x2	2.2	10	21
1.5x2.5	2.9	15	15
1.5x3	4.9	15	21
1.6x3.17	5.5	15	20
2x4	8.8	15	21
2.5x4	7.2	25	14
3x5	11.8	25	15
3.3x6.35	21.7	30	20
3.5x6	17.5	30	16
4x6	14.7	40	12
4x8	35.4	30	21
4.35x6.35	15.8	45	11
5x7	17.7	55	10
5x8	28.8	45	14
6x8	20.6	70	9
6x10	47.2	50	15
6.35x9.52	37.10	60	12
6.5x10	42.6	60	13
7x9	23.6	90	7
7x10	37.6	75	11
8x10	26.5	115	7

8x12	59	75	12
9x12	46.5	105	9
9.52x12.7	52.10	115	9
10x12	32.5	165	5
10x14	70.9	105	10
11x14	55.3	150	7
12x15	59.8	170	7
12x16	82.7	140	9
12.5x15	50.7	210	5
14x18	94.5	180	7
14x20	150.6	145	11
15x18	73.10	250	5
16x20	106.3	225	7
18x25	222.3	195	10
20X26	203.8	250	8
21X25	135.9	360	5
22X26	141.8	390	5
25X32	294.7	330	7
26X32	257	390	6