

SPIRALS IN RILSAN PA11 PHL WITH TANKS

HOSES › Hoses for Pneumatic Applications › SPIRAL AND/OR CONNECTED HOSES

For operating pressures as a function of temperatures, see linear tube table.

To avoid deformations we recommend using RILSAN spirals within the temperatures: -20°C +80°C.

Useful length: 50% max 60% of the linear meters is recommended.

Standard colours: orange, blue.



Mastertubi.it/q?273

Code	Ø mm	Pipe length m	At rest mm	Maximum usage m	Terminal length mm	Maximum operating pressure at 20°C
01SRCH0002/04	2x4	2.5	90	1.5	100	44
01SRCH02.5/04	2.5x4	2.5	90	1.5	100	30
01SRCE0004/06	4x6	7.5	252	5	130	26
01SRCD0004/06	4x6	10	340	6.5	130	26
01SRCC0004/06	4x6	15	515	10	130	26
01SRCE0006/08	6x8	7.5	285	5	130	19
01SRCD0006/08	6x8	10	390	6.5	130	19
01SRCC0006/08	6x8	15	586	10	130	19
01SRCE0008/10	8x10	7.5	280	5	170	14
01SRCD0008/10	8x10	10	380	6.5	170	14
01SRCC0008/10	8x10	15	565	10	170	14
01SRCE0010/12	10x12	7.5	240	5	180	12
01SRCD0010/12	10x12	10	350	6.5	180	12
01SRCC0010/12	10x12	15	535	10	180	12
01SRCD0012/15	12x15	10	285	6	200	14
01SRCC0012/15	12x15	15	436	10	200	14
01SRCD0014/18	14x18	10	300	6	200	16
01SRCC0014/18	14x18	15	470	10	200	16
01SRCD0015/18	15x18	10	470	6	200	12
01SRCC0015/18	15x18	15	470	10	200	12