

SILICONE HOSE VMQ+FKM 230 C green

HOSES › Silicone rubber hoses and sleeves

Silicone hoses in VMQ (Vinyl Methyl Quality) with high temperature resistant aramid fiber textile reinforcements and fluorinated elastomer (FKM) sublayer.

APPLICATIONS

Connection between turbine and intercooler on cars, trucks, industrial vehicles and generators, for the passage of petrol, oils and chemical products (solvents).

Operating temperatures: -30° up to 230°C

ISO 1307 reference standards for WALL dimensional tolerances +1/-0.50mm

Standard lengths 1000mm

Color Green (RAL6038)

Shore A hardness 65-75



Mastertubi.it/q?1208

Internal diameter mm	Wall thickness mm	Number of polyester reinforcements	Burst pressure (bar)
6.5	4	3	32.5
8	4	3	32.5
9.5	4	3	32.5
11	4	3	27
13	4	3	27
16	4	3	27
19	4	3	19.3
22	4	3	19.3
25	4	3	19.3
28	4.5	3	19.3
30	4.5	3	13.1
32	4.5	3	13.1

35	4.5	3	13.1
38	4.5	3	15.4
40	4.5	3	15.4
45	4.5	3	12.6
48	4.5	3	12.6
51	5	4	12.6
54	5	4	12.6
57	5	4	13.4
60	5	4	13.4
63	5	4	13.4
65	5	4	13.4
68	5	4	8
70	5	4	8
76	5	4	8
80	5	4	8
83	5	4	5.50
90	5	4	5.50
102	5	4	5