

## SILICONE SLEEVE HT/NMX 250 C - 45 BEND

HOSES › Silicone rubber hoses and sleeves

### APPLICATION:

sleeves usable in air conditioning systems of civil and industrial vehicles, cogeneration units, marine engines, high temperature fluid transport.

### CHARACTERISTICS:

smooth in appearance externally and internally, not corruptible by antifreeze liquids or rust.  
Excellent resistance to pressure, thermal aging and oxidizing agents (oxygen, ozone and UV rays)  
Resistant to hardening the tube is resistant to compressive forces.  
Ideal for use at high **temperatures between -60° and 250°C, it can reach temperatures up to 275°C for short periods of time** .

### CONSTRUCTION:

Construction material: VMQ silicone rubber (Vinyl Methyl HT) compliant with EU directive 2002/95/ECC for the restriction of the use of hazardous substances (RoHS). Structure reinforced with triple layer of ARAMID fiber fabric, contoured shape 45° curves.  
BRICK RED COLOR. Wall thickness 3.70 mm - tolerance +1/-0.5mm.

### LIMITATIONS:

compliance with the declared values, not suitable for the continuous passage and storage of hydrocarbons (even if resistant to traces of oil and diesel).  
It is not suitable for use at high vacuum, nor for transporting abrasive powders.

CODES	DESCRIPTION
10SILI250NOMEX45_032	SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø 32
10SILI250NOMEX45_035	SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø 35
10SILI250NOMEX45_040	SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø 40
10SILI250NOMEX45_045	SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø 45
10SILI250NOMEX45_050	SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø 50
10SILI250NOMEX45_055	SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø 55
10SILI250NOMEX45_060	SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø 60
10SILI250NOMEX45_065	SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø 65
10SILI250NOMEX45_070	SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø 70
10SILI250NOMEX45_076	SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø 76
10SILI250NOMEX45_080	SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø 80
10SILI250NOMEX45_088	SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø 88
10SILI250NOMEX45_090	SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø 90

10SILI250NOMEX45\_100

SILICONE SLEEVE HT/NMX 250°C red - CURVED 45° - SHANK 150 - 3 plies Ø  
100