

## CAMLOCK FEP-SILICONE CORE GASKET

FITTINGS FOR AGRICULTURAL-INDUSTRIAL MAINTENANCE › CAM LOCK FITTINGS

ELASTIC SEAL FOR CAM LOCK FEMALE FITTING IN FEP (Fluorinated Ethylene Propylene) WITH SILICONE HEART Weight 40 g - RED COLOR - compliant with RoHs and REAC

DN	INTERNAL DIAMETER mm	OUTER DIAMETER mm	THICKNESS mm
1/2"	16.00 +/- 0.3	26.30 +/-0.3	4.00 +/-0.10
3/4"	22.22 +/- 0.3	34.93 +/-0.3	5.54 +/-0.10
1"	26.99 +/- 0.3	39.69 +/-0.3	6.35 +/-0.10
1"1/4	34.53 +/- 0.3	49.21 +/-0.3	6.35 +/-0.10
1"1/2	41.27 +/- 0.3	55.56 +/-0.3	6.35 +/-0.10
2"	50.80 +/- 0.3	66.67 +/-0.3	6.35 +/-0.10
2"1/2	60.32 +/- 0.3	79.37 +/-0.3	6.35 +/-0.10
3"	76.20 +/- 0.4	94.45 +/-0.4	6.35 +/-0.10
4"	101.30 +/- 0.4	123.30 +/-0.4	6.35 +/-0.10
5"	127.00 +/- 0.4	150.30 +/-0.4	6.35 +/-0.10
6"	152.40 +/- 0.5	179.83 +/-0.5	6.35 +/-0.10
8"	237.00 +/- 0.5	237.30 +/-0.5	9.50 +/-0.10



[Mastertubi.it/q?970](http://Mastertubi.it/q?970)