

## EXTRAFLEX 1185 CRT POLYURETHANE HOSE

HOSES › Compressed air hoses

Linear hose in self-lubricated antistatic polyurethane with textile reinforcement, multilayer flexible ether-based polyurethane resistant to hydrolysis and microbial corrosion. Internal reinforcement with glued high tenacity POLYESTER FIBER braid, rhombic mesh for maximum resistance to pressure.

Hardness 85 shoreA - Operating temperature: -40° +60°C

Excellent pressure resistance pressure safety factor: 3:1

Recommended for use with hose barb fittings and clamps.

Available colors: BLUE - RED

PACKAGING: ROLLS OF 100 meters - CARDBOARD BOX IN ROLLS OF 25 - 50 METERS

Code	Dimension mm	Weight g/m	Radius of curvature mm	Pressure exercise Cafe	colors
03EX90TR5.5/8 2	5.5x8	30.5	40	13	blue-red
03EX90TR6.5/10	6.5x10	52.2	40	20	blue
03EX90TR7.5/10	7.5x10	39.4	55	40	blue
03EX90TR8/12	8x12	72.3	50	20	blue-red
03EX90TR10/14.5	10x14.5	99.7	70	15	blue
03EX90TR11/16	11x16	122.2	75	15	blue
03EX90TR13/18	13x18	140.2	100	15	blue
03EX90TR13/19	13X19	173.8	85	15	blue