

PVC SEWAGE HOSE

HOSES › Water intake hoses

Very flexible general purpose plastic hose for medium to heavy duty.

Very robust with external shock-proof rigid PVC spiral. Completely smooth internal surface, smooth external surface. High suction resistance.

Resistant to the action of atmospheric agents and most chemical products.

Operating temperature: -25°C +60°C

Vacuum value: 9 meters of water column.

Suitable for heavy-duty uses where extreme flexibility is required, ideal for industrial liquid suction, irrigation, well purging, waste water purging.

COLOR: gray with blue spiral.



Mastertubi.it/q?280

| Item number | Dimension Ø mm | Weight gr/m | Curvature radius mm | Operating pressure bar | Rolls m |
|---------------|-------------------|----------------|------------------------|------------------------------|------------|
| 04PLIQ0000025 | 25 | 500 | 100 | 7 | 50 |
| 04PLIQ0000032 | 32 | 600 | 130 | 6 | 50 |
| 04PLIQ0000038 | 38 | 700 | 150 | 6 | 50 |
| 04PLIQ0000040 | 40 | 800 | 160 | 6 | 50 |
| 04PLIQ0000045 | 45 | 900 | 180 | 5.5 | 50 |
| 04PLIQ0000050 | 50 | 1050 | 200 | 5 | 50 |
| 04PLIQ0000060 | 60 | 1250 | 240 | 4.5 | 50 |
| 04PLIQ0000063 | 63 | 1390 | 240 | 4.5 | 50 |
| 04PLIQ0000070 | 70 | 1550 | 280 | 4 | 50 |
| 04PLIQ0000076 | 76 | 1700 | 300 | 4 | 50 |
| | | | | | |

| | | | | | |
|---------------|------|-------|-----|-----|----|
| 04PLIQ0000080 | 80 | 1850 | 320 | 3.5 | 30 |
| 04PLIQ0000090 | 90 | 2250 | 360 | 3.5 | 30 |
| 04PLIQ0000102 | 102 | 2700 | 400 | 3 | 30 |
| 04PLIQ0000110 | 110 | 3100 | 440 | 3 | 30 |
| 04PLIQ0000120 | 120 | 3600 | 480 | 2.5 | 20 |
| 04PLIQ0000125 | 125 | 3900 | 510 | 2.5 | 20 |
| 04PLIQ0000130 | 130 | 4100 | 520 | 2.5 | 20 |
| 04PLIQ0000152 | 152 | 5000 | 610 | 2 | 20 |
| 04PLIQ0000160 | 160 | 5600 | 640 | 2 | 20 |
| 04PLIQ0000200 | 200* | 10000 | 800 | 1.5 | 10 |

(*) DN 200 - SUPPLIED ONLY IN FLEXIBLE RODS 10 METERS LONG.