

APOLLO PVC SEWAGE HOSE

HOSES › Water intake hoses

Very flexible plastic hose for general uses for medium-heavy duty. Very robust with external shock-proof and crush-proof rigid PVC spiral. Completely smooth internal surface, corrugated external surface. High resistance in suction and delivery. Resistant to the action of atmospheric agents and most chemical products.

Suitable for heavy-duty uses where extreme flexibility is required even at low temperatures.

Ideal for suction of industrial liquids on tank trucks and drain trucks, irrigation, well draining, sewage draining.

Operating temperature: -25° C +60° C.



Mastertubi.it/q?294

| item | Diameters Ø mm | Weight g/m | Radius of curvature mm | operating pressure Cafe | aspiration Cafe | rolls |
|--------------|-------------------|---------------|------------------------------|-------------------------------|--------------------|-------|
| 04APOLLO0025 | 25 | 410 | 100 | 6 | 0.10 | 50 |
| 04APOLLO0032 | 31.8 | 590 | 130 | 6 | 0.10 | 50 |
| 04APOLLO0038 | 38.1 | 690 | 155 | 5 | 0.10 | 50 |
| 04APOLLO0040 | 40 | 720 | 160 | 5 | 0.10 | 50 |
| 04APOLLO0050 | 50 | 980 | 200 | 4 | 0.10 | 50 |
| 04APOLLO0060 | 60 | 1230 | 240 | 4 | 0.90 | 50 |
| 04APOLLO0063 | 63.5 | 1390 | 260 | 4 | 0.90 | 50 |
| 04APOLLO0070 | 70 | 1620 | 280 | 3 | 0.90 | 50 |
| 04APOLLO0076 | 76.2 | 1730 | 310 | 3 | 0.90 | 50 |
| 04APOLLO0080 | 80 | 1885 | 320 | 3 | 0.90 | 50 |
| 04APOLLO0090 | 90 | 2200 | 360 | 3 | 0.90 | 30 |
| 04APOLLO0102 | 102 | 2830 | 410 | 3 | 0.85 | 30 |

| | | | | | | |
|--------------|-------|------|-----|-----|------|----|
| 04APOLLO0110 | 110 | 2885 | 410 | 3 | 0.85 | 30 |
| 04APOLLO0120 | 120 | 3410 | 480 | 2.5 | 0.80 | 30 |
| 04APOLLO0127 | 127 | 3670 | 510 | 2.5 | 0.80 | 30 |
| 04APOLLO0152 | 152.4 | 5280 | 610 | 2 | 0.80 | 20 |
| 04APOLLO0160 | 160 | 5670 | 660 | 2 | 0.70 | 20 |
| 04APOLLO0200 | 200 | 9900 | 850 | 1.5 | 0.70 | 10 |