

SAE J 517 HOSE: SAE 100 R4 FUEL

HOSES › Hydrocarbon suction hoses

Hose suitable for the delivery of mineral oils, hydraulic fluids and fuels in hydraulic systems compliant with SAE J 517: SAE/100 R4 standard.



Tube in smooth black NBR antistatic rubber resistant to hydrocarbons with low aromatic content (<50%), with textile reinforcement and incorporated steel spiral and copper cord for attachment.



Mastertubi.it/q?1004

Black CR/NBR rubber cover with cloth finish, resistant to hydrocarbons, atmospheric agents and abrasion.

SUCTION: 0.80 bar

Operating temperature: -40° +100° C.

40 - 20 meter rolls

Marking: red stripe - FUEL OIL - SD -SAE/100 R4 J517 WP PSI

Øi mm	Øe mm	Pressure of work Cafe	Pressure of explosion Cafe	Radius of curvature mm	roll m
13	23	10	30	50	40
16	26	10	30	50	40
19	29	21	84	50	40
22	32	10	30	70	40
25	35	17	68	70	40
30	41	10	30	90	40
32	43	14	56	90	40
35	46	10	30	100	40
38	49	10	30	100	40
10	52	10	30	120	40

42	54	10	30	120	40
45	57	10	30	120	40
48	60	10	30	130	40
51	63	10	30	135	40
55	67	10	30	180	40
60	74	10	30	340	40
63.5	77	10	30	340	20
70	84	10	30	420	20
76	90	10	30	460	20
80	96	10	30	480	20
90	106	10	30	520	20
102	118	10	30	610	20
120	139	10	30	810	20
127	146	10	30	900	20