

CANALKLER 250 S

HOSES › FLEXIBLE HOSES FOR LIQUID SUCTION, WELL CLEANING, AGRICULTURE

Specific flexible rubber hose for heavy-duty sewerage and high-pressure water washing.

Specific features of this product:

- Low flow resistance: higher speed in the sewer
- Longer lifespan
- Aramid reinforcement: greater safety



Advantages

Very low creep resistance which allows: greater cleaning efficiency, reduction of cleaning times and therefore reduction of fuel consumption. Greater durability thanks to the special covering compound with greater abrasion resistance. Better flexibility, even at low temperatures. Easy to handle and easy to use. Resistance to deformation. High resistance and safety thanks to the aramid reinforcement.

Inner tube: SBR, smooth, black.

Reinforcement: aramid fabric, woven.

Cover: SBR / NR, smooth. Very low creep resistance, black.

Working temperature range: -30° to +80° C

ZH 1/406 Approval (Guidelines for Fluid Spray Jets).

Additional Information

Supplied with test certificate on each factory assembled hose.

Joint fittings

All hoses are assembled with BSP female/BSP male.

All hose assemblies are pressure tested to 375 bar and have a unique hose number.



Masterubi.it/q?1120

ID (mm)	OD(mm)	Operating pressure (bar)	Burst pressure (bar)	Bending radius (mm)	Weight (kg/m)	Length (m)	Item number
13	25.6	250	625	70	0.45	40	5014178
13	25.6	250	625	70	0.45	60	5014179
13	25.6	250	625	70	0.45	80	5014180
13	25.6	250	625	70	0.45	100	5014916
13	25.6	250	625	70	0.45	120	5014005
19	31.6	250	625	90	0.61	40	5014181
19	31.6	250	625	90	0.61	80	5014182
19	31.6	250	625	90	0.61	100	5014459
19	31.6	250	625	90	0.61	120	5014006
25	39.3	250	625	100	0.9	40	5014183
25	39.3	250	625	100	0.9	50	5014874
25	39.3	250	625	100	0.9	80	5014184
25	39.3	250	625	100	0.9	100	5014238

25	39.3	250	625	100	0.9	120	5014007
25	39.3	250	625	100	0.9	150	5014461
25	39.3	250	625	100	0.9	160	5014185
25	39.3	250	625	100	0.9	180	5014186
25	39.3	250	625	100	0.9	200	5014520
25	39.3	250	625	100	0.9	240	5014733
32	47.6	250	625	130	1.12	40	5014187
32	47.6	250	625	130	1.12	80	5014188
32	47.6	250	625	130	1.12	120	5014008
32	47.6	250	625	130	1.12	150	5014466
32	47.6	250	625	130	1.12	160	5014189
32	47.6	250	625	130	1.12	180	5014190
32	47.6	250	625	130	1.12	200	5014655
38	54	250	500	155	1.35	120	5014009