

ARMORVIN HNP TUBE

HOSES › FLEXIBLE HOSES FOR LIQUID SUCTION, WELL CLEANING, AGRICULTURE

Transparent plasticized PVC tube with built-in galvanized steel spiral. marking with green stripe. Suitable for contact with foods according to DDC, milk and derivatives at low temperatures. Smooth surfaces, high flexibility, good abrasion resistance.

OPERATING TEMPERATURE: -5° +65° C

COMPLIANT WITH THE FOLLOWING EUROPEAN LEGISLATION:

- Directive 1978/142/EEC
- Regulation 1935/2004/EC
- Regulation 1895/2005/EC (EPOXY DERIVATIVES)
- Regulation 2023/2006/EC (GMP)
- Regulation 10/2011/EU and subsequent updates



Mastertubi.it/q?1195

COMPLIANT WITH THE FOLLOWING ITALIAN LEGISLATION:

- Ministerial Decree 03/21/1973 and subsequent updates and amendments
- Presidential Decree no. 777 of 08/23/1982 and subsequent updates and amendments.

OR inch	OR <i>internal</i> mm	OR <i>external</i> mm	empty at 23° <i>m/H₂O</i>	Operating pressure 23° <i>Cafe</i>	Burst pressure 23° <i>b ar</i>	Curvature radius mm	Weight meter <i>g/m</i>	roll <i>m</i>
3/8"	10	16	9.5	8	24	20	155	60
	12	18	9.5	8	24	25	180	60
	14	20	9.5	8	24	30	200	60
5/16"	16	22	9.5	8	24	35	225	60
	18	24.5	9.5	7	21	40	280	60
	20	27	9.5	7	21	50	340	60

7/8"	22	29	9.5	6	18	55	360	60
1"	25	33	9.5	6	18	60	510	60
	30	39.5	9.5	5	15	70	680	60
1"1/4	32	41.5	9.5	5	15	75	730	60
	35	44	9.5	5	15	80	730	60
1"1/2	38	49	9.5	5	15	90	950	30
	40	53	9.5	5	15	100	1220	30
1"3/4	45	58	9.5	5	15	110	1400	30
	50	64	9	5	15	125	1600	30
	60	74	9	5	15	140	2050	30
2"1/2	63	77	9	4	12	150	2250	30
	70	86	9	4	12	180	2600	30
	75	91	9	4	12	200	2850	30
	80	96	9	3	9	220	3150	30
	90	107	9	3	9	260	3750	30
4"	100	118	9	3	9	300	4400	30
	105	122	9	2	6	310	4000	20
	110	128	9	3	9	320	4650	20
	120	138	9	2	6	340	5200	20
	125	144	9	2	6	350	5400	20
	150	170	9	2	6	450	7200	20
	203	223	9	2	6	900	9900	clips