


GALVANIZED METALFLEX SFC

HOSES › Flexible metal pipes

Flexible hot-dip galvanized steel hose with ecofibre gasket for medium and low pressures, cold air extraction and conveyance systems, paper scrap suction. Single seam version according to UNI EN ISO 15465:2005



Compressive strength: 4

Impact resistance: 4

Minimum temperature -40° C: 5

Maximum temperature +300° C: 6

Flexible curvature without position maintenance, it is not self-supporting.

IP54 protection ACCORDING TO CEI EN 60529

Medium corrosion resistance

Tensile strength Ø 28 - 50: 4

Tensile strength Ø 55-250: 5

Zero flame propagation

RoHS - REACH: yes

Material DX 51D/Z100 galvanized steel



Mastertubi.it/q?1165

Diameter internal mm	Diameter external mm	Radius of curvature mm	Weight Kg/m
20	24	124	0.45
25	29	153	0.55
30	34.3	182	0.65
35	39.3	252	0.91
40	49.3	154	0.94
45	50	154	0.94
50	55	171	1.04
55	60	187	1.14
60	65	203	1.24
70	75	208	1.40
80	85	221	1.49
85	90	234	1.58
90	95	248	1.67
95	100	261	1.76
100	102	382	2.46
110	115	419	2.70
115	120	437	2.82

120	125	456	2.94
125	130	475	3.06
130	135	493	3.18
135	140	512	3.29
140	145	530	3.41
150	155	568	3.65
160	165	691	4.59
170	175	733	4.87
180	185	776	5.16
200	205	861	5.72
250	255	1073	7.14