

TANK WAGON TUBE

HOSES › Hydrocarbon delivery hoses

Hose suitable for the delivery suction of fuel, mineral oil, ecological petrols, with an aromatic solvent content of less than 50%.

Extremely flexible and light structure with minimal bending radii considering the rubber hose. Normally supplied with tankers for the transport of automotive or heating fuels.



-Smooth antistatic black NBR rubber tube ($R < 10^6 \text{ O}$)



-Highly resistant textile inserts and incorporated steel spiral, with copper cable suitable to guarantee electrical continuity.

- Anti-static corrugated black anti-abrasive rubber cover

($R < 10^6 \text{ O}$) 



Mastertubi.it/q?288

Operating temperature

-30° +80°C - maximum peaks of 120° C depending on the fluids conveyed

Operating pressure: 5 bar

safety factor greater than three times the operating pressure

Maximum depression -0.90 bar

Maximum roll length 40 metres.

Available in use sizes with smooth sleeves at the ends.

item	Dimensions	Dimensions	Radius of	Weight
	Internal Ø	External Ø	curvature	
	mm	mm	mm	Kg/m
06GBTANK00032	32	43	100	0.90
06GBTANK00038	38	50	120	1.10

06GBTANK00040	40	52	120	1.15
06GBTANK00045	45	59	150	1.48
06GBTANK00050	50	64	180	1.60
06GBTANK00063	63.5	77.5	250	2.05
06GBTANK00070	70	85	280	2.43
06GBTANK00076	76	91	300	2.60
06GBTANK00080	80	95	320	2.73
06GBTANK00090	90	106	360	3.34
06GBTANK00100	100	116	400	3.67
06GBTANK00102	102	118	400	3.73