

## MARINE FUEL FUEL HOSE - RINA

HOSES › Hydrocarbon delivery hoses

**BLACK RUBBER HOSE FOR SUPPLY OF FUEL, DIESEL, BIO-DIESEL, ECOLOGICAL PETROL OF INBOARD ENGINES ON PLEASURE BOATS UP TO 24 METERS.**



**Tube:** smooth black NBR rubber resistant to fuels with an aromatic content not exceeding 50%, bio-diesel, ecological petrols with a maximum content of oxygenated compounds of 15%.

**Reinforcements:** high resistance synthetic fabrics.

**Cover:** in self-extinguishing black CR/NBR rubber resistant to abrasion, heat, fuels, ozone and marine agents.

**Surface:** smooth with canvas finish.

**Temperature:** -20° +80° C



Mastertubi.it/q?928

Marking:

Price list red writing: CARBOPOMP MARINE FUEL ISO 7840:2013 A1 E10/B10 COMPATIBLE CE -SAE J 1527:2011 USCG A1 - ABYC - RINA - LLOYD'S REGISTER (YEAR-DIAM.INT).

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESSIONE SCOPPIO BURST PRESSURE		RAGGIO CURVATURA BENDING RADIUS		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	mm	inch	mt	ft
6	1/4"	15	9/16"	0.26	0.17	>14	>210	30	1.18"	20/40	65.5/131
8	5/16"	16	5/8"	0.27	0.18	>14	>210	45	1.77"	20/40	65.5/131
10	3/8"	18	3/4"	0.30	0.20	>14	>210	55	2.17"	20/40	65.5/131
12	1/2"	21	7/8"	0.43	0.29	>10	>150	70	2.76"	20/40	65.5/131
16	5/8"	25	1"	0.50	0.34	>10	>150	90	3.54"	20/40	65.5/131
19	3/4"	29	1.5/32"	0.64	0.43	>10	>150	130	5.12"	20/40	65.5/131
25	1"	37	1.15/32"	0.87	0.58	> 10	> 150	250	9.84"	20	65.5
30	1.3/16"	42	1.21/32"	1.00	0.67	> 10	> 150	300	11.81"	20	65.5
32	1.1/4"	44	1.23/32"	1.05	0.71	> 10	> 150	320	12.60"	20	65.5
35	1.3/8"	47	1.27/32"	1.15	0.77	> 10	> 150	350	13.78"	20	65.5
38	1.1/2"	52	2.1/16"	1.55	1.04	> 10	> 150	380	14.96"	20	65.5
40	1.9/16"	54	2.1/8"	1.60	1.08	> 10	> 150	400	15.75"	20	65.5
45	1.3/4"	59	2.5/16"	1.80	1.21	> 10	> 150	450	17.72"	20	65.5
51	2"	65	2.9/16"	1.95	1.31	> 10	> 150	500	19.69"	20	65.5
60	2.3/8"	74	2.29/32"	2.08	1.39	> 10	> 150	600	23.62"	20	65.6