

## MULTIPURPOSE RIBBED RUBBER HOSE

HOSES › Nautical hoses - Off-shore umbilical hoses

Pipe for passing hot water mixed with antifreeze liquids, in car radiators, engine cooling systems, heating circuits of vehicle cabins, due to its flexibility it is particularly suitable for the engine compartment.

Appearance: Smooth black exterior with canvas impression, smooth black interior with corrugated outside, black color.

Construction: Heat-resistant EPDM synthetic rubber, inserted metal spiral, synthetic textile reinforcements, grooved EPDM cover for extreme flexibility, resistant to aging and weathering.

Compliant with ISO 1307/1992.

Operating temperature:  $-40^{\circ}$   $+120^{\circ}$  C.

Maximum operating pressure 5 bar, safety factor 3.

Maximum depression 0.80 bar. 40 metre rolls.

On request, execution of sleeves at the ends.



[Mastertubi.it/q?346](http://Mastertubi.it/q?346)

Item code	Dimensions Ø mm	Curvature radius mm
09GGREMU015/023	15x23	55
09GGREMU018/028	19x27	70
09GGREMU020/030	20x28	70
09GGREMU022/032	22x30	75
09GGREMU025/035	25x33	85
09GGREMU028/038	28x36	95

09GGREMU030/040	30X38	100
09GGREMU032/042	32x40	105
09GGREMU035/045	35x45	115
09GGREMU038/048	38x47	130
09GGREMU040/050	40x49	135
09GGREMU045/055	45x54	150
09GGREMU050/060	50x60	165
09GGREMU060/070	60x70	200
09GGREMU63,5/73,5	63.5x73.5	220
09GGREMU076/086	76x86	250
09GGREMU080/090	80x92	270
09GGREMU090/100	90x102	300
09GGREMU102/113	102x117	400