

HYGIENIC-SHIP HOSE

HOSES › Nautical hoses - Off-shore umbilical hoses

Flexible rubber hose suitable for the suction and delivery of waste water, biological tanks on board ships, bilge pumps. Internal structure in black type IIR rubber, or white on request, smooth, particularly resistant to the transmission of odors and the formation of bacterial forms. Textile reinforcements with high tenacity synthetic fabrics and incorporated metal spiral. White EPDM rubber cover with cloth finish, non-toxic, resistant to abrasion and atmospheric agents, compliant with Ministerial Decree 21.03.73 and subsequent amendments and with the FDA



Mastertubi.it/q?350

Working temperature: $-35^{\circ} + 90^{\circ}$ C.

Vacuum tightness 0.8/0.7 bar

Available versions: cord, smooth spiral, corrugated spiral, corrugated with sleeves at the end in use pieces.

L/BB □ SMOOTH WHITE EXTERIOR/SMOOTH WHITE INTERIOR with two textile reinforcements with steel spiral

L/N.BI □ SMOOTH WHITE EXTERIOR/SMOOTH BLACK INTERIOR with two textile reinforcements with steel spiral

O/N.BI □ WAVY WHITE EXTERIOR/SMOOTH BLACK INTERIOR with two textile reinforcements with steel spiral

Dimension OR mm	Radius of curvature mm	Pressure of exercise Cafe
19x29	57	10
25x35	75	10
30x40	90	10

32x42	90	10
35x45	105	10
38x48	114	8
40x50	120	8
45x55	135	6
51x61	150	6
60x71	180	5