

HEAT PIPE/10 LL

HOSES › Hot water hoses

Flexible black EPDM rubber hose for hot water delivery up to 120°C at a maximum pressure of 10
Log Length Structure.

APPLICATION: Delivery of hot water and medium aggressive refrigerant fluids, used in the cooling
heating circuits of cars. Also excellent for low pressure washing

TUBE: Black, smooth EPDM rubber

REINFORCEMENT: High tenacity fabrics

COVER: Black, smooth EPDM rubber, resistant to abrasion, ozone and atmospheric agents

WORKING TEMPERATURE: -40°C +120°C

diameter internal	diameter external	Weight	Pressure of work	Pressure of explosion	Roll
mm	mm	kg/m	Cafe	Cafe	m
5	11	0.12	10	30	100
6	13	0.14	10	30	100
8	15	0.17	10	30	100
9	16	0.17	10	30	100
10	17	0.18	10	30	100
12	19	0.22	10	30	50
13	20	0.24	10	30	50
14	22	0.27	10	30	50
15	23	0.32	10	30	50
16	23	0.29	10	30	50
18	26	0.37	10	30	50
19	27	0.39	10	30	50
20	28	0.42	10	30	50
22	30	0.51	10	30	50
25	34	0.60	10	30	50