

BERGALAV. PIPE

HOSES › Hot water hoses

Flexible rubber hose suitable for cleaning, with hot water, food industry processing plants with possible occasional use of steam up to a maximum temperature of 160°C.
Highly flexible. Particularly suitable if installed on a hose reel. Does not contain phthalates.

Food grade, smooth, white EPDM rubber tube.
Synthetic fabric reinforcement
Weather-resistant EPDM compound cover, smooth, blue
Operating temperature range: -30° to +160° C



Mastertubi.it/q?1435

Standards and approvals:

EU Regulations n. 1935/2004, 2023/2006.

FDA Regulation No. 21 CFR 177.2600 for French Legislation.

All relevant migration tests (France and FDA) were performed by the French Institute of Poitiers (IANESCO) and confirmed compliant.

internal diameter (mm)	external diameter (mm)	Operating pressure (Cafe)	Burst pressure (bar)	Bending radius (mm)	Weight per meter (kg/m)	Roll Length (m)
10 ±0.6	18 ±0.7	10	30	75	0.25	20
10 ±0.6	18 ±0.7	10	30	75	0.25	40
13 ±0.6	22 ±0.7	10	30	95	0.35	20
13 ±0.6	22 ±0.7	10	30	95	0.35	40
16 ±0.7	25 ±0.8	10	30	110	0.41	20
16 ±0.7	25 ±0.8	10	30	110	0.41	40
19 ±0.8	29 ±0.9	10	30	135	0.54	20
19 ±0.8	29 ±0.9	10	30	135	0.54	40
25 ±1.0	36 ±1.0	10	30	180	0.74	20
25 ±1.0	36 ±1.0	10	30	180	0.74	40